

### Moving cuff and moving elbow sensor in BPBIO750 help

patients wear the cuff correctly even without managers.

This is InBody's unique technology that induces correct posture for accurate measurement value.



The moving cuff helps wear accurately, even if the person's posture is not correct.



The moving elbow sensor leads the elbow to correct position by sensing the contact of the elbow

\* Patent registration number: 10-2016-0036313

### Excellent visibility is fundamental!

The guide-display helps blood pressure measurement to be convenient even alone.

This guide-display guides the sequence of blood pressure measurement.

You can easily measure blood pressure, according to guide from BPBIO750 without medical personnel.



### **BPBI0750** Specifications

#### Core specifications

Measurement Method Oscillometric method

Automatic adjustment by air pressurization speed controller and micro pump Pressurization Pressurization method Decompression method Automatic adjustment by air decompression speed controller and micro valve Decompression

Exhaust Automatic rapid exhaust method

Cuff Pressing belt system by geared motor, automatic operation

0~300 mmHg(Pressure), 30~240 bpm(Pulse), 17~42 cm(Arm circumference) Range of measurement

Degree of precision Pressure  $\pm 2$  mmHg, pulse within  $\pm 1.5\%$ 

Systolic blood pressure, diastolic blood pressure, pulse rate, pulse pressure, mean blood pressure, rate pressure product Measurement results

Measurement time Approx. 30 seconds on average (20-50 seconds depending on the pulse and blood pressure value)

Minimum scale unit

### Functional specifications

Display method (Screen type) 7-Segment LED

Display contents Measurement guide, elbow detection, measurement result value, irregular blood pressure signal detection, and time

Human body detection sensor A sensor to detect human presence in front of device

Moving elbow sensor Equipped with a fluid structure for the accurate elbow detection (Patent registered)

Moving cuff Equipped with a fluid structure to induce accurate measurement posture

Result Sheets Selectable for measurement values, graph, common sense for blood pressure, or correct posture guide

Error display Outputting error message on Results Sheets and display screen

Checking the number of

measurements

The number of measurements per day, the total number of cumulative measurements

Voice guidance Guiding the blood pressure measurement and the result after measurement

Background music Playing background music when adjusting volume

High-speed thermal printer with the built-in automatic cutter (width: 2.5-inch) Printer

Two Start/Stop buttons in front and rear bottom sides, Start/Stop button

Emergency stop button Emergency stop button in front bottom side

Safety mechanism Quick cuff release and exhaust by pressing the Start/Stop button

Automatically release and exhaust the cuff when the air pressure exceeds 300 mmHg

Quick cuff release and exhaust by pressing the Emergency stop button

(The dual safety mechanism enables the cuff to release and exhaust regardless of the central controller when the Emergency

stop button is pressed.)

RS232C External interface

Accessories Dedicated desk, height-adjustable dedicated chair

### Other specifications

Power source AC 100~120 / 200~240V, 50 / 60Hz, 48VA Dimensions Approx. 299 (W) × 547 (D) × 485 (H) mm

Display screen size Approx. 200(W) x 135(H) mm

Weight Approx. 7.1 kg (Package weight: Approx. 11.3 kg) Desk: Approx. 12.0 kg, Chair: Approx. 5.3 kg Optional device

Operating 10~40°C, 30~75% RH, 70~106 kPa

-10~70°C, 10~80% RH(No Condensation), 50~106 kPa

- \* For purposes of improvement, specifications are subject to change without notice
- \* This product is a 'medical equipment'. Please read the guide and cautions before using

this blood pressure monitor

### Certifications and patents acquired by InBody

InBody is the first body composition analyzer in Korea to obtain the European and Japanese meter approval and holds a total of about 80 patents worldwide











MDSAP













### InBody HQ [KOREA]

InBody Co., Ltd.

625, InBody Bldg., Eonju-ro, Gangnam-gu, Seoul 06106 Republic of Korea

TEL: +82-2-501-3939 FAX: +82-2-578-5669 Website: inbody.com E-mail: info@inbody.com





# **BPBI0750**

The automatic blood pressure monitor inducing correct measurement posture



### Moving cuff, Moving elbow sensor

Inducing correct posture for correct measurement

### **Smart Interface**

Convenient interface to measure personally, even without managers

### **Measurement of both arms**

Convenient to measure both arms with the ergonomic design

## Automatic blood pressure monitor



### Simple and sophisticated four point colors



## **BPBIO750** features

1 Moving cuff Inducing correct posture in close contact with measuring arm

2 Moving elbow sensor Inducing correct settlement of the elbow by reflecting the shape of measuring arm

3 Guide-display Convenient Interface for personal measurement

4 Convenient to measure both arms with the ergonomic design

**5** Large screen Excellent visibility for systolic blood pressure, diastolic blood pressure, and pulse rate

**6** Selectable Result Sheets

Pulse envelope, blood pressure result graph, confirmation of measurement posture, the common sense of blood pressure, and logo are insertable when printing selectable type of Result Sheets.

Basic Result Sheets

Small Result Sheets InBody

DIA

75

2023.06.27

115 mmHa

 $75_{\text{mmHg}}$ 75 bpm

2023.06.27

PUL

75

InBody

SYS

DIA

**PULSE** 

SYS

115

Result Sheets to select output options

DIA 75 mmHg M.A.P 88 mmHg P.P 40 mmHg PULSE 75 bpm R.P.P 8625 Pulse Envelope	0.10		
M.A.P 88 mmHg P.P 40 mmHg PULSE 75 bpm R.P.P 8625 Pulse Envelope  Sloge 1 hypertransion  Sloge 3 hypertransion  Sloge 3 hypertransion	SYS	115 mmHg	
M.A.P 88 mmHg P.P 40 mmHg PULSE 75 bpm R.P.P 8625 Pulse Envelope	DIA	75 mmHg	
PULSE 75 bpm R.P.P 8625 Pulse Envelope  Signal amenda in religials, tale the measurement again. Blood Pressure graph	M.A.P		
R.P.P. 8625  Pulse Envelope	P.P	40 mmHg	
Pulse Envelope  150 30m; 150 1vor rudae sendayo ii of miguda basi the massacrend again. Blood Pressure graph  50p; 50p; 50p; 50p; 50p; 50p; 50p; 50p;	PULSE	75 bpm	
Slow)  Slow Pressure graph  Slow Slow Pressure graph  Slow Slow Style St	R.P.P	8625	
Fixor pulse errekça is ret reçukr, take the messurerest spain.  Blood Pressure graph  Stage 3 Hypertension  Stage 2 Hypertension	Pulse Envelope———		
DIA Stage 3 Hypertension  Stage 2 Hypertension	(mineq) (mineq)		
Stage 3 Hypertension  Stage 2 Hypertension	Blood Pressure graph ———		
Stage 2 Hypertension	DIA (mridg) St	age 3 Hypertension	

InBody	2023.06.27	
SYS	115 mmHg	
DIA	75 mmHg	
M.A.P	88 mmHg	
P.P	40 mmHg	
PULSE	75 bpm	
RPP	8625	
Pulse Envelope  30 156  Fyou plue envelope is not regaler, who the measurement regards.		
Blood Pressure graph ———		
Operation   Stage 3 Hypertension		
Reference: ESC-ESH Guide	ine for the management	



Blood pressure knowledge Blood pressure fluctuates constant! Take three blood pressure measure ments to obtain your average.

InBody



**8** Automatic power saving function Entering to sleep mode when waiting more than 2 minutes

9 Easy to control back button for administrator Convenient Start/Stop button on front and back of BPBIO750

10 Irregular pulse wave detection







Gray



